

## Specifications:

Insulation resistance : 0.01M $\Omega$  to 2.0G $\Omega$

Auto- Discharge of capacitive voltage : 0.01M $\Omega$  to 2.0G $\Omega$

Insulation test smoothing reading : 0.01M $\Omega$  to 2.0G $\Omega$

Frequency : 0.01M $\Omega$  to 2.0G $\Omega$

Capacitance : 0.01M $\Omega$  to 2.0G $\Omega$

Diode Test: 0.01M $\Omega$  to 2.0G $\Omega$

Temperature : 0.01M $\Omega$  to 2.0G $\Omega$

Min / Max: 0.01M $\Omega$  to 2.0G $\Omega$

VFD Low- low pass filter for accurate motor  
drive measurements: 0.01M $\Omega$  to 2.0G $\Omega$

AC / DC Voltage : 0.01M $\Omega$  to 2.0G $\Omega$

DC Multivolts : 0.01M $\Omega$  to 2.0G $\Omega$

AC / DC Miliamps: 0.01M $\Omega$  to 2.0G $\Omega$

Resistance : 0.01 $\Omega$  to 2.0M $\Omega$

Continuity : 0.01 $\Omega$  to 2.0M $\Omega$

Auto Power Off : 0.01 $\Omega$  to 2.0M $\Omega$