SUPPLEMENTAL/ BID BULLETIN

Republic of the Philippines
Calamba Water District
Lakeview Subd, Halang, Calamba City
Tel. Nos: (049) 545-2728; 545-1614; 545-1389
Fax No: (049) 545-9752/502-7108
E-mail add: cwd bac@yahoo.com

ADDENDUM NO. 1

16 April 2025

AMENDMENTS TO BIDDING DOCUMENTS

Under Section I. Invitation to Bid. Paragraph 2, Section VI. Specifications, Scope of Works and Specifications, Item No. III. Restoration, Asphalt Pavement Restoration, Construction Requiements, Bullet Nos. 1, 12 and 13, therof should be read as follows:

- I. Invitation to Bid. Paragraph 2, should be read as follows:
 - The Calamba Water District now invites bids for the above Procurement Project.
 Completion of the Works is required within Fifteen (15) Days to deliver Fifteen (15)
 Batches (10 metric tons per batch) of hot asphalt. Bidders should have completed a contract similar to the Project. The description of an eligible bidder is contained in the Bidding Documents, particularly, in Section II (Instructions to Bidders).
- II. Section VI. Specifications, Scope of Works and Specifications, Item No. III. Restoration, Asphalt Pavement Restoration, Item No. 4. Construction Requiements, Bullet Nos. 1, 12 and 13, should be read as follows:

ITEM No. III. RESTORATION

Asphalt Pavement Restoration

4. Construction Requirements

- Hot Asphalt Mix shall be placed only when the specified density can be obtained. The mixture shall not be placed on any wet surface or when weather condition will prevent its proper handling or finishing. Asphalt surface mixture shall not be placed when the surface temperature of the base course is below 100°C
- Sampling sampling of asphalt materials shall be in accordance with the latest revision of AASHTO Designation T40 (ASTM Designation D140). Sampling of mineral aggregate shall be in accordance with the latest revisory AASHTO designation (ASTM Designation D 75). Sampling of the asphalt mixture, as required by the Engineer, shall be in accordance with the latest revision of AASHTO Designation 168 (ASTM Designation D 979).
- Testing Methods of Testing shall be in accordance with the applicable AASHTO or ASTM Methods.

The Contractor will shoulder the testing fee.

The Contractor may perform one (1) of the following recommended asphalt testing:

1. Marshall Test

- 2. Superpave Gyratory Compactor Test
- 3. Wheel-Tracking Test
- 4. Penetration Test
- 5. Softening Point Test
- 6. Specific Gravity Test
- 7. Viscosity Test

For guidance and information of all concerned.

ENGR. JOSELITO A GILLERA

BAC Chairperson

Received by:	
Date:	

Supply of Labor and Asphalt Materials for the Restoration Works at Brgy., Bucal to Bagong Kalsada, Calamba City (CWD 13-2025)