

SPECIFICATIONS

1. Temperature Screening Face Terminal

7-inch LCD touch screen, 2 Mega pixel wide-angle lens
Built-in Mifare card reading module; Max 6,000 faces capacity; Max. 6,000 cards; verification methods: supporting fast temperature measurement and face/card recognition with fever screening
Authentication distance : 0.3-1.8 m
Temperature range: 30-45 C
Supports 6 attendance status, including check in, check out, break in , break out, overtime in, overtime out
Face recognition duration (1:N) 2s
Mask detection: supporting face mask wearing alert and forced mask wearing alert without proper supply

The mounting pole for DS-K1T671TM-3XF
Material: SPCC
Weight : 6.7 kg(14.8 lbs)
Dimension (W x H x D) : 98.5 mm x 1342 mm x 2225 mm (3.9 x 52.8 x 8.9) without power

2. Screen Temperature with Monitor

BULLET CAMERA	<p>Thermal: 160 x 120 Lens: 6 mm FOV: 25" x 18.7" Optical: 2688 x 1520 Lens : 8 mm Video Mode: Bi -spectrum image fusion Accuracy: 10.5 C Range : 30-45 C Working Temperature: 10-35 C</p>
NVR	<p>320 Mbps Bit Rate Input Max (up to 16-ch IP video), 4 SATA Interfaces, up to 8TB per HDD, alam 1/0:16/8, 1.5 U case, 19"</p>
SWITCH	<p>L2, Unmanaged, 4 10/100M RJ45 PoEports, 1 10/100M RJ45 uplink port, 802.3 af/at, PoE power budget 60W, max. 250m long distance transmission, 6KV surgy protection</p>
ACCESSORY	<p>UNC 1/4" - 40 tripod connection Bullet tripod adapter 4TB/64MB/Intell power (RPM) SATA 3</p>
ACCESSORY	<p>Bullet tripod adapter</p>
ACCESSORY	<p>4TB/64MB/Intell power (RPM) SATA 3</p>
MONITOR	<p>31.5" 1080P, HDMI/VGA input, view angle : 178', 300cd/m, plastic casing, VESA, base bracket included, 7'24h</p>