Supply and Delivery of Conference Microphone with Complete Accessories

SPECIFICATIONS

Amplifier

- POWER AMPLIFIER
- 2 X 800W @ 8 ohms
- 2 X 1200W @ 4 ohms
- 2400W @ 8 ohms Bridge

8 Channel Wireless Conference Microphone System

- 2 X 800W @ 8 Ohms
- 2 X 1200 @ 4 Ohms
- 2400W @ 8 Ohms Bridge

- Quality wireless conference microphone system
- 8X100 Selectable frequencies on each channel, up to 30 units can be used simultaneously
- Automatic transmitter setup, the channel of the transmitter and receiver can easily synchronize
- 8 XLR individual outputs and one 1/4" Mixed output
- Range: up to 300 Feets (100 meters), Frequency: UHF 530MHz - 580MHz

Channel Mixer with Bluetooth and Antares

- Selectable Hi Pass Filter on first 4 inputs
- 3-band EQ on all channels
- 4 channels of Peavey's exclusive MidMorph® EQ
- EQ bypass per channel
- 2 channels of built-in compression
- Individual channel mutes
- Individual Listen/Solo function
- LED clip and signal present indication
- 4 Channels of direct out
- Stereo pan control per channel
- Channel 5/6 stereo 1/4", RCA, or 3.5mm input channel
- Dual selectable control room outputs
- One pre-fader AUX send
- KOSMOS bass and treble enhancement
- Main stereo outputs with 1/4" unbalanced and balanced XLR connectors
- Precision 60 mm faders on master
- High quality master LED meter bridge
- Master mic mute
- Studio quality headphone output
- Equipped with Bluetooth wireless connectivity, Bluetooth 3.0 + EDR, A2DP
- On-board USB-A MP3 and WAV playback
- Stereo USB-B streaming audio in and out, 16-bit, up to 48kHz sample rates
- Built-in Digital Effects with LCD Display
- Peavey's exclusive on-board Hi Z guitar input
- Global 48V phantom power
- Product Dimensions: 12.75" wide x 15.1" deep x 2.1875" high (32.39 cm x 38.35 cm x 5.56 cm)
- Weight Packed: 9.48 lb(4.3 kg)
- Width Packed: 16.14"(40.9956 cm)
- Height Packed: 16.54"(42.0116 cm)
- Depth Packed: 3.54"(8.9916 cm)

Four (4) pieces – Two (2) way full range passive loud speaker

10" Passive Speaker System
Provide Excellent Vocal and Bass Performance
Rugged Plastic Mold Design Cabinet
Bottom Pole Mount for Tripod Stand
Multiple Handle for Easy Transport
90° by 60° Wave Guide Horn for Wide Coverage

Multi Angle Enclosure can also use as a monitor
Easy Daisy-Chain Loop Connections
System Type: 2 Way Bass Reflex
LF: 10" Woofer (2" Voice Coil Size)
HF: 1" Titanium Dome Tweeter
Freq. Res.: 48Hz - 20kHz
Impedance: 8 Ohms
Power: 350W
Sensitivity: 97 dB
Air Duct: Front
Inputs: 2 NL4 Speak ON

Professional Cabinet 12U Mobile Flight Box – Aluminum Material

12U Professional Tourcase Power Amplifier Audio Cabinet Mixer Rack Mobile Audio Chassis with Plexiglass Door Package includes: 1 pc 12u Cabinet Rack

40m HDMI Cable Super Long Active Cable

- Built-in active booster.
- HDMI High Speed with Ethernet Cable.
- Individually Screened Cable.
- HDMI Ethernet Channel.
- Audio Return Channel.
- 3D over HDMI.
- 1080p Resolution Support.
- Expanded Support for Colour Spaces.
- Micro USB socket TV end to apply optional extra power if required.

Data Transfer Cable

Brand Name	FJGEAR
ConnectorA	VGA
Connector B	VGA
Cable Length	40 M
Type	Data Transfer Cable
Application	Projector,Multimedia,Television,Monitor,Computer
Packing	Polybag

HDMI to VGA Cable Converter

- Without Audio Ccable
- HDMI INput : the HDMI INput interface
- VGA Output:VGA signal Output interface
- HDMI to VGA cable converts HDMI digital video and audio signals into analog of the VGA interface and audio output.
- Convert the HDMI output port on your ENVY or Voodoo laptop to an analog VGA input with the HDMI to VGA Conversion Adapter.
- It supports full-size high-definition resolution of 720p or 1080p.
- Can use for All HDMI input and VGA output device.
- Computer Accessories
- For computer set
- For desktop computer set

TF Wire - #18

Wall Mount

- Comes in Pair (2pcs.)
- Up to 50KG Speaker Capacity
- Standard Fit to all Speaker's with Hole
- Swiveling Wall Mounting Bracket
- Adjustable Horizontal Angle
- For Wall Mounting Professional Speakers with Pole Mount.
- Heavy Duty