



Calamba Water District

Lakeview Subdivision, Halang, Calamba City, Laguna

Tel. Nos. 545-1614; 545-2728; 545-7895; 545-1389; 545-7981

Fax: (049) 545-9752

CAMERA AND LENS SPECIFICATIONS FOR THE OFFICE OF THE GENERAL MANAGER

Camera/Video Camera

Megapixel & Sensor	24.3MP FX-Format CMOS Sensor
Mount	Nikon F mount, (with AF coupling and AF contacts)
LCD Screen	3.2" Rear Screen Tilting LCD (1,229,000)
Video Recording	1920 x 1080p (Full HD) / 1280 x 720p (HD)
Flash	Built-In: Auto / Auto/Red-Eye Reduction / Fill-In / Hi-Speed Sync / Off / Rear Curtain/Slow Sync / Rear Sync / Red-Eye Reduction / Slow Sync / Slow Sync/Red-Eye Reduction
External Flash	Hot Shoe
Focus	Auto / Manual / Continuous Auto
ISO	Auto, 100-12800 (Extended Mode: 50-51200)
Continuous Shooting	Up to 6.5 fps
Shutter Speed	1/4000-, 30s, in steps of 1/3 or 1/2 EV, bulb, time, X200
Touch Screen	No
Wireless Functions	Wireless remote controllers: WR-1, WR-R10 (available separately). Supports WPS. WiFi: Authentication: Open system, WPA2-PSK Encryption: AES
Viewfinder	Eye-level pentaprism single-lens reflex viewfinder
Card Slot	Double slot: Slot 2 can be used for overflow or backup storage or for separate storage of copies created using NEF+JPEG; pictures can be copied between cards. SD / SDHC / SDX /


Lens

Filter Size Front: 77 mm
Max Magnification 0.24x
Focal Length 24 - 120mm
Focus 1.48' (45 cm)
Aperture Maximum: f/4; Minimum: f/22
Angle of View 84° - 20° 20'
Dimension (diameter x length) Approx. 3.31 x 4.07" (84 x 103.5 mm)

General

Color Black
Product Dimension Approx. 140.5, x113, x78mm (5.6, x4.5, x3.1in.)
Warranty 2 Years Manufacturer
Battery EN-EL15 rechargeable Li-ion battery

Prepared by:


Engr. Jonathan Dave A. Fajarda
Management Information Design Specialist A

Approved by:


Engr. Restituto B. Sumanga, Sr.
General Manager