



Calamba Water District

Lakeview Subdivision, Halang, Calamba, Laguna
Tel. Nos. 545-2863, 545-1614, 545-7895, 545-1389
Tel./Fax. (049) 545-9752

POWER GENERATOR SET

*Two (2) units - 25 Kva, standby rating, Three (3) Phase, 230VAC
60Hz., 1800rpm, 0.8P.F*

GENERAL DESCRIPTION:

Trailer mounted mobile Genset, heavy duty steel frame with vibration isolators, base fitted fuel tank with capacity capable for eight (8) hrs. continuous operations at full load, Soundproof weather protective enclosure and complete with standard accessories.

ENGINE AND ALTERNATOR:

4-Cylinder, In-line, turbocharged, aftercooled, 4 stroke cycle, direct injection, electronic actuated governor, water radiator cooling system, electric starting, Close coupled to A/C brushless alternator, self-exciting, self-regulating, Insulation Class H, Single bearing and with Built in Automatic Voltage Regulator.

CONTROL PANEL :

Digital Control Panel with display of all parameters; Equipped with Automatic Shut-Off sensors for engine low-oil pressure, high coolant temperature, over-crank, over/under speed and over/under frequency. Also equipped with EMERGENCY push Button Shut – off Switch..

Prepared by:

Pedro M. Estalar
Water Maintenance Head

Approved by:

Engr. Joselito A Gillera
Production Dept. Manager